Artificial Intelligence formulated this projection for compatibility purposes from the original article published at Global Journals. However, this technology is currently in beta. *Therefore, kindly ignore odd layouts, missed formulae, text, tables, or figures.* 

# Supervised Content based image Retrieval using Fuzzy Texton and Shearlet Transform Sudhakar Putheti<sup>1</sup>, Mohan Krishna Kotha<sup>2</sup> and Srinivasa Reddy Edara<sup>3</sup> <sup>1</sup> Acharya Nagarjuna University Received: 12 December 2014 Accepted: 1 January 2015 Published: 15 January 2015

### 7 Abstract

In this paper we proposed, a novel framework to assist and automate the diagnosis of diseases
from computer-based image analysis method using Content-based image retrieval (CBIR).
CBIR is the process of retrieving related images from large database collections by using low
level image features such as color, texture and shape etc. we have used fuzzy texton and
discrete shearlet transform to extract texture and shape features. The aim is to support
decision making by retrieving and displaying relevant past cases visually similar to the one
under examination with relevance feedback using Support Vector Machines.

15

16 Index terms— content based medical image retrieval, fuzzy texton, texels, and support vector machines.

# 17 **1 Introduction**

he digital imaging revolution in the medical domain over the past three decades has changed the way that the present-day physicians diagnose and treat diseases. These images of various modalities are playing an important role in detecting the anatomical and functional information about different body parts for the diagnosis, medical research, and education. Modern medical information systems need to handle these valuable resources effectively and efficiently. Currently, the utilization of medical images is limited due to the lack of effective search methods; text-based searches have been the dominating approach for medical image database management [1,2].

Content-based image retrieval (CBIR), also known as query by image content (QBIC) and content based visual information retrieval (CBVIR) is the application of computer vision to the image retrieval problem. Research in content-based image retrieval (CBIR) today is an extremely active discipline. There are already review articles containing references to a large number of systems and description of the technology implemented [1,2]. A more recent review [3] reports a tremendous growth in publications on this topic. Applications of CBIR systems to medical domains already exist [4], although most of the systems currently available are based on radiological images.

When referred to text retrieval based on keyword, current technique has already met the demand of the users expectation. As to the demand of digital multimedia retrieval in the network, for instance image, video and many other digital multimedia retrieval. Nowadays there also have some digital multimedia format's search engines which are special for image and mp3 format, for example Google image search engine, but the retrieval methods of these search engines still use the techniques based on text and keywords match. The goal is to retrieve the images based on visual features such as color, texture and shape.

Formerly developed commercial content-based image retrieval systems characterized images by global features such as color histogram, texture values and shape parameters, however, for medical images, the systems using global image features failed to capture the relevant information [5].

Color is one of the most widely used low-level visual features and is invariant to image size and orientation [6]. Various texture representations have been investigated in pattern recognition and computer vision. Basically, texture representation methods can be classified into two categories: structural and statistical. Structural methods, including morphological operator and adjacency graph, describe texture by identifying structural primitives and their placement rules [7]. They tend to be most effective when applied to textures that are very regular. Statistical methods, including Fourier power spectra, co-occurrence matrices, Zernike moments,
shift-invariant principal component analysis (SPCA), Markov random field, fractal model, and multiresolution
filtering techniques such as Gabor and wavelet transform, characterize texture by the statistical distribution of

48 the image intensity [8].

Shape has been one of the most important and effective low level visual features in characterizing much pathology identified by medical experts [9]. The use of shape as a feature is less developed than the use of color or texture, mainly because of the inherent complexity of representing it [10]. Yet, retrieval by shape has the potential of being the most effective search technique in many application fields [11].

Support Vector Machines (SVM) [12] is an approximate implementation of the structural risk minimization 53 (SRM) principle. It creates a classifier with minimized Vapnik-Chervonenkis (VC) dimension. SVM minimizes 54 an upper bound on the generalization error rate. The SVM can provide a good generalization performance on 55 pattern classification problems without incorporating problem domain knowledge. One key design task, when 56 constructing image databases is the creation of an elective relevance feedback component. While it is sometimes 57 possible to arrange images within an image database by creating a hierarchy, or by handlabeling each image 58 with descriptive words, it is of-ten time-consuming, costly and subjective. Alternatively, requiring the end-user 59 60 to specify an image query in terms of low level features (such as color and spatial relationships) is challenging to 61 the end-user, because an image query is hard to articulate, and articulation can again be subjective.

Recent trials for content-based medical image retrieval were ASSERT system [13] for high resolution computed tomography (CT) images of the lung and image retrieval for medical applications (IRMA) system [14] for the classification of images into anatomical areas, modalities and viewpoints. Flexible image retrieval engine (FIRE) system handles different kinds of medical data as well as non-medical data like photographic databases **??**15].

The rest of the paper is organized as follows. In Section II, the proposed image retrieval method steps fuzzy texton detection, shear wavelet transform and support vector machines (SVM) for relevance feedback and texels calculation are discussed. Section III, Experiments, performance evaluations, and discussions are given.

### 69 2 II.

### 70 3 Proposed Method

An efficient image retrieval technique is required to improve the success rate with the rapid increase in the usage of digital media. The block diagram of the proposed CBIR system is shown in Figure 1.

# <sup>73</sup> 4 a) Extraction of Fuzzy Texton Images

Fuzzy Texton is a way to describe the texture property further better than the Texton since Fuzzy texton uses the fuzzy texture unit (FTU) instead of texture unit (TU). By including fuzzy concept to the texton will generates all ranges of the values including '2' in the FTU [16,17]. Then, it helps to generates different textures are 5 8 instead of 4 8. The main idea of the proposed method (TFT) is, Texton images are obtained by applying the 12 types of 3 x3 texton templates [18].

As per Julesz description a texton is a pattern which is shared by an image as a common property [19]. 79 Textures which can be decomposed into elementary units, the texton are formed only if the adjacent elements lie 80 within the neighborhood. The critical distances between texture elements which depend on the texture element 81 size are used to incline the texton. Textons are classes of colors, elongated blobs of specific width, orientation, 82 aspect ratios and terminators of elongated blobs. If texture elements are greatly expanded in one orientation, 83 discrimination reduces. If the elongated elements are not jittered in orientation, texture gradients increase at 84 boundaries. Thus with a small sub image of size 3 x 3 is used to obtain texton gradient. In the previous proposed 85 technique TFT [18], we have proposed 12 textons of 3 x 3 grids. The computational complexity for using the 86

# <sup>87</sup> 5 Global Journal of C omp uter S cience and T echnology

Volume XV Issue I Version I Year () overlapped components of 12 textons is also less to obtain final texton
 image.

<sup>90</sup> The basic unit of the method is defined by a central pixel and its eight neighbors, forming a 3x3 pixel square.

<sup>91</sup> This minimal square image has the local texture information of the central pixel in all the directions.

In our case the size of the neighborhood is 3x3 pixels. This pattern of the image, consisting by 9 pixels, is denoted by a set V of nine elements,  $V = \{V \ 0 \ , V \ 1 \ , V \ 2 \ ? \ V \ 8 \}$ , where V 0 represents the intensity value of the central pixel and V i (1?i?8) the intensity value of each neighboring pixel. The smallest complete unit which best characterizes the local texture aspect of a given pixel and its neighborhoods, in all eight directions of a square raster, is Texture Unit (TU) that is defined, by TU={E 1 , E 2 , ?, E 8 }, where: E i = ? ? ? ? ? 0 if V i < V 0 and V i < ?? 1 if V i < V 0 and V i > ?? 2 if V i = V 0 ; 3 if V i > V 0 and V i < ?? 4 if V i > V 0 and V i > ?? 1 ? i ? 8 (1)

here p and q are user defined values and each element E i occupies the same position as pixel i. An example is shown in Figure 1. As to each element of the TU can be assigned one of three possible values 0, 1,2,3 or 4, the total number of Texture Units is  $5 \ 8 = 16777216$ . These Units can be labeled and ordered in different ways; here we will label each TU as a 5-base number, named Texture Unit Number, N TU according to next formula: N TU = 2 E i 2 i 1 2 8 i=1 (2)

Where the position of the Texture Unit box and E i is the value of the box (0, 1, 2, 3 or 4). Moreover, the 8 elements can be ordered differently. If they are ordered clockwise, as shown in Figure 1(c), the first element can take eight possible positions, from the top left a to the middle left h, and then the 16777216 texture units can be labeled by the abode formula under eight different ordering ways (from a to h).

A more detail study of texture unit indicates that the absent TU's involve two's in their texture unit. This is the case when neighbors and central pixels have the same values. If there is a lack of two's then TU will take only 0,1,3 and 4 which means that the possible real number of different textures are 4 8 instead of 5 8, that is 65536 and 390625 the spectrum will be never totally covered, thus the power of the method is misused. It impacts on texture Unit number also. To overcome this, fuzzy texture is used in the proposed method. Fuzzy Texton is a way to describe the texture property further better than Texton.

Fuzzy Texton is a way to describe the texture property further better than the Texton since Fuzzy texton uses the fuzzy texture unit (FTU) instead of texture unit (TU). By including fuzzy concept to the texton will generates all ranges of the values including '2' in the FTU [20]. Then, it helps to generates different textures are 5 8 instead of 4 8. It covers total spectrum which is not possible by texton only (means without fuzzy) [21]. The main idea of the proposed method (TFT) is, Texton images are obtained by applying the 12 types of 3 x3 texton templates [22] as shown in figure 4 on HSV planes as shown in figure 3.

We used the Fuzzy Texture unit boxes (FTUB) and Fuzzy Texture Unit Numbers (FTUN) which are used by 120 Aina Barceló. et. al [20]. In this proposed work, FTUB and FTUN are used during the period of quantifying the 121 texton images. Then, the resultant textons are called as fuzzy texton images. Using fuzzy techniques provide 122 a more flexible way of assigning values (E i ) to the TU boxes. From now on E i will not be a unique value 123 0, 1, 2, 3 or 4, but it will have the five values associated at the same time, each one to its own degree. Each 124 particular degree will be calculated with the aid of a membership function that has to be defined. Therefore, we 125 will consider Fuzzy Texture Unit Boxes (FTUB) FE i that are defined as follows:???? ?? = {?? 0 (?? ?? ), ?? 1 126 (?? ?? ), ?? 2 (?? ?? ), ?? 3 (?? ?? ), ?? 4 (?? ?? )}, 1 ? ?? ? 8(3) 127

Where in ? 0 (V i ),? 1 (V i ),? 2 (Vi ), ? 3 (V i ) and ? 4 (V i ) are the membership degrees of V i [20] to the fuzzy sets 0, 1, 2, 3 and 4 respectively. In a similar way to the TU, the Fuzzy Texture Unit (FTU) is defined by: Global Journal of C omp uter S cience and T echnology Volume XV Issue I Version I Year ()????? = {???? 1, ???? 2, ???? 3, ???? 4, ???? 5, ???? 6, ???? 7, ???? 8 } (4)

As part of the detection process of fuzzy texton, our 3 x 3 grids can detects the textons in all directions and also corners of the textures. If three pixels are highlighted and have the same value then grid will form a fuzzy texton as shown in Figure 5.

### <sup>135</sup> 6 b) Edge Orientation using Discrete Shearlet Transform

The approach used in this paper is based on a new multiscale transform called the shearlet transform. It is 136 multidimensional version of the traditional wavelet transform, and is especially designed to address anisotropic 137 and directional information at various scales. Indeed, the traditional wavelet approach, which is based on isotropic 138 dilations, has a very limited capability to account for the geometry of multidimensional functions. In contrast, the 139 analyzing functions associated to the shearlet transform are highly anisotropic, and, unlike traditional wavelets, 140 are defined at various scales, locations and orientations. As a consequence, this transform provides an optimally 141 efficient representation of images with edges [23]. The shearlet transform has similarities to the curvelet transform, 142 Shearlets and curvelets, in fact, are the only two systems which were mathematically known to provide optimally 143 sparse representations of images with edges and the implementations of the curvelet transform correspond to 144 145 essentially the same tiling as that of the shearlet transform. Both systems are related to contourlets [26], [27] and steerable filters [28], [29]. We refer to [30] for more details about the comparison of shearlet and other orientable 146 multiscale transforms. 147

In this paper, we combine the shearlet framework with several well established ideas from the image processing 148 literature to obtain improved and computationally efficient algorithms for edge analysis and detection. Our 149 approach may be viewed as a truly multidimensional refinement of the approach of Mallat et al., where the 150 isotropic wavelet transform is replaced by an anisotropic directional multiscale transform. As a result, the shearlet 151 transform acts as a multiscale directional difference operator and provides a number of very useful features: 152 Improved accuracy in the detection of edge orientation. Using anisotropic dilations and multiple orientations, 153 the shearlet transform precisely captures the geometry of edges. It is a multiscale transform, based on the same 154 affine mathematical structure of traditional wavelets. The discretization of the shearlet transform provides a 155 stable and computationally efficient decomposition and reconstruction algorithm for images. An algorithm for 156 157 edge detection based on shearlets was introduced in [24,25], where a discrete shearlet transform was described 158 with properties specifically designed for this task. In fact, the discrete shearlet transform which was presented above for image denoising, produces large side lobes around prominent edges which interfere with the detection 159 of the edge location. By contrast, the special discrete shearlet transform introduced in [24,25] is not affected by 160 this issue since the analysis filters are chosen to be consistent with the theoretical results in [31,32], which require 161 that the shearlet generating function ? satisfies certain specific symmetry properties in the Fourier domain. 162

163 The first step of the shearlet edge detector algorithm consists in selecting the edge point candidates of a digital

image u[m1,m2]. They are identified as those points (?? 1 ????, ?? 2 ????) which, at fine scales j, are local
maxima of the function?? ?? ??[?? 1, ?? 2 ] 2 = ? ??????[??, ??, ?? 1, ?? 2 ] ? 2 ?? (5)

Here ??????[??, ??, ?? 1, ?? 2] denotes the discrete shearlet transform. According to the properties of the continuous shearlet transform summarized above, we expect that, if (?? 1 ????, ?? 2 ????) is an edge point, the discrete shearlet transform of u will behave as a straight of the shearlet transform of u will behave as a straight of the shearlet transform of u will behave as the shearlet transform of u wi

Where ?? 0. If, however, ? < 0 (in which case the size of |SHu| increases at finer scales), then (?? 1????, ?? 2 169 ????)will be recognized as a spike singularity and the point will be classified as noise. Using this procedure, edge 170 point candidates for each of the oriented components are found by identifying the points for which ?? 0. Next, 171 a non-maximal suppression routine is applied to these points to trace along the edge in the edge direction and 172 suppress any pixel value that is not considered to be an edge. At each edge point candidate, the magnitude of 173 the shearlet transform is compared with the values of its neighbors along the gradient direction (this is obtained 174 from the orientation map of the shearlet decomposition). If the magnitude is smaller, the point is discarded; if 175 it is the largest, it is kept. Extensive numerical experiments have shown that the shearlet edge detector is very 176 competitive against other classical or state-of-the-art edge detectors, and its performance is very robust in the 177 presence of noise. An 178

## <sup>179</sup> 7 Global Journal of C omp uter S cience and T echnology

Volume XV Issue I Version I Year () example is displayed in Figure 12, where the shearlet edge detector is
compared against the wavelet edge detector (which is essentially equivalent to the Canny edge detector) and the
Sobel and Prewitt edge detectors. Notice that both the Sobel and Prewitt filters are 2D discrete approximations
of the gradient operator. The performance of the edge detectors is assessed using the Pratt's Figure of Merit,
which is a fidelity function ranging from 0 to 1, where 1 is a perfect edge detector. This is defined as?????? = 1
?????? (?? ?? ?? ?? )? 1 1+???? (??) 2

?? ?? ??=1 (7) where ?? ?? is the number of actual edge points, ?? ?? is the number of detected edge points, d(k) is the distance from the k-th actual edge point to the detected edge point and ? is a scaling constant typically set to 1/9. The numerical test reported in the figures show that the shearlet edge detector consistently yields the best value for FOM.

Once this is found, the corresponding angle of orientation ?? ?? ?(??, ??) associated with the index ?? ?(??, 197 ??)can be easily computed. As illustrated in [25], this approach leads to a very accurate and robust estimation for 198 the local orientation of the edge curves. To illustrate the general principle, consider the simple image in Figure 199 13 consisting of large smooth regions separated by piecewise smooth curves. The junction point A, where three 200 edges intersect, is certainly the most prominent object in the image, and this can be easily identified by looking 201 at values of the shearlet transform. In fact, if one examines the discrete shearlet transform ??????[?? 0, ???, ?? 0 202 ], at a fixed (fine) scale ?? 0 and locations?? 0, as a function of the shearing parameter l, the plot immediately 203 identifies the local geometric properties of the image. Specifically, as illustrated in Figure 13(b), one can recognize 204 the following four classes of points inside the image. At the junction point ?? 0 = ??, the function |????????? 0, 205 ??, ?? 0] exhibits three peaks corresponding to the orientations of the three edge segments converging into A; 206 at the point ?? 0 = ??, located on a smooth edge, |????????? 0, ??, ?? 0| has a single peak; at a point ?? 0 207 = ??, inside a smooth region, |??????[?? 0, ??, ?? 0]| is essentially flat; finally, at a point ?? 0 = ??"close" to 208 an edge, [??????[?? 0, ??, ?? 0]] exhibit two peaks, but they are much smaller in amplitude than those for the 209 points A and B. A similar behaviour was observed, as expected, for more general images, even in the presence of 210 noise. Based on these observations, a simple and effective algorithm for classifying smooth regions, edges, corners 211

and junction points of an image was proposed and validated in ??52].

# <sup>213</sup> 8 c) Support Vector Machine for Relevance Feedback

Consider the binary classification problem  $\{(x_i, y_i)\}$ , for i=1 to N, where xi are the labeled patterns and yi? 214 215  $\{?1, +1\}$  the corresponding labels. Based on this training set, we want to train an SVM classifier. The SVM 216 classifier maps the patterns to a new space, called kernel space, using a transformation x? (x), in order to get a 217 potentially better representation of them. This new space can be nonlinear and of much higher dimension than 218 the initial one. After the mapping, a linear decision boundary is computed in the kernel space. In the context of SVM methodology, the problem of classification is addressed by maximizing the margin, which is defined as the 219 smallest distance, in the kernel space, between the decision boundary and any of the training patterns. This can 220 221 ?? ?? =1 ?? ??=1 222

<sup>223 ?? ?? ?? ?? ?? ?? ?? ?? ?? ?? ??</sup> over ?? ?? , i=1,?,N

- 224
- Where?????? ?? , ?? ?? ?? = ??(?? ?? ) ?? ?????? ?? ?(11) 225

is the kernel function and C is a parameter controlling the trade-off between training error and model 226 complexity. The most popular non-linear kernel functions used for SVMs belong to the class of Radial Basis 227 Functions (RBFs). From all RBF functions, the most commonly used is the Gaussian RBF, which is defined 228 229

After the training of the classifier, the value of the decision function for a new pattern x is computed by:??(??) 230 = ? ?? ?? ?? ?? ??=1 ?? ?? ??(?? ?? , ??) + ??231

Where b is a bias parameter the value of which can be easily determined after the solution of the Year ( 232

) optimization problem [33]. The value |y(x)| is proportional to the distance of the input pattern x from the 233

decision boundary. Thus, the value y(x) can be regarded as a measure of confidence about the class of x, with 234

- large positive values (small negative values) strongly indicating that x belongs to the class denoted by +1 (?1). 235
- On the contrary, values of y(x) around zero provide little information about the class of x. 236

### 9 d) Extraction of Texels 237

After the extraction of fuzzy texton images need to extract the texels from them. The local properties [18] used to 238 extract the feature vectors used here come under two categories: one is regarding color information and other is 239 about texture. Some of the important features of texture properties (cluster properties) are Local Homogeneity, 240 Cluster Shade and Cluster Prominence. 241

- 242
- 243

(18) In the framework of CBIR with RF, in each round of RF we have to solve a classification problem as 244 the one described above, where a number of images, represented as feature vectors, correspond to the feedback 245 examples provided by the user so far, and each image is labeled by ?1 or +1 corresponding to irrelevant or 246 relevant, respectively. The initial query is considered to be one of the relevant images and is labeled by +1. 247 From the above, it is obvious that we can train an SVM classifier based on the feedback examples and use it to 248 distinguish between the classes of relevant and irrelevant images. Each image in the database will be presented 249 to the trained classifier and the value of the decision function (Eq. (??)) will be used as the ranking criterion. 250 The higher the value of the decision function for an image, the more relevant this image is considered by the 251 system. III. 252

### **Results and Discussion** 10 253

The effectiveness of the proposed retrieval system is evaluated on fundus image database, Skin cancer image 254 database and Endoscopy image database. The sample images from the fundus image database are shown in the 255 figure 5. We can use different distance metrics for matching such as an N-dimensional feature vector  $\mathbf{F} = [F1, F1]$ 256 F2...FN]. It is extracted from every image of database and stored in database. Let Q = [Q1, Q2, Q3, ?, QN] be the 257 feature vector of query image. A simple distance measure [34] whose time complexity is very less when compared 258 with others like Euclidean (no square or square root operations) when we consider large databases, is given by (F, 259 Q) = ? |F i ?Q i | 1+F i +Q i N i=0(19)260

### b) Performance Measure 11 261

Most common measurements are used to evaluate the performance of image retrieval methods are Precision, 262 Recall and Accuracy curves [35]. 263

Precision ??(??) = ?? ?? ?? (20) Recall ??(??) = ?? ?? ?? (21) Accuracy ??(??) = (??(??) + ??(??)) 2 (22)264 Where I N is the number of images retrieved in the top N positions that are similar to the query image and M 265 is the total number of images in the database similar to the query image. In all cases the framework provides 266 higher precision, recall and accuracy. 267

### Global Journal of C omp uter S cience and T echnology 12268

Volume XV Issue I Version I Year () 269

<sup>&</sup>lt;sup>1</sup>© 2015 Global Journals Inc. (US)

 $<sup>^{2}</sup>$ © 2015 Global Journals Inc. (US) 1



Figure 1: Figure 1 :



Figure 2: Figure 2 :







Figure 4: Figure 4 :









No.5



No.9





No.2

No.10





No.3

No.11



2. 1

No.8

No.4

0





Figure 6: Figure 5 :



Figure 7: Figure 6 :



Figure 8: Figure 7 :

- 270 [Aachen (ed.) ()], Germany Aachen. Rheinisch-Westfalische Technische Hochschule Aachen (ed.) 2003.
- 271 [M"uller et al. ()] 'A review of content-basedimage retrieval systems in medical applications -clinical benefits
- and future directions'. H M"uller, N Michoux, D Bandon, A Geissbuhler. International Journal of Medical
   Informatics 2004. 73 p. .
- 274 [Yi et al. ()] 'A Shearlet approach to edge analysis and detection'. S Yi , D Labate , G R Easley , H Krim . IEEE275 Trans. Image Proc 2009. 18 (5) p. .
- 276 [Shyu et al. ()] 'ASSERT A physician-in-theloop contentbased retrieval system for HRCT image databases'. C
- R Shyu , C E Brodley , A C Kak , A Kosaka , A M Aisen , L S Broderick . Computer Vision and Image
   Understanding 1999. 75 (1/2) p. .
- [Guo and Labate ()] 'Characterization and analysis of edges using the continuous shearlet transform'. K Guo ,
   D Labate . SIAM J. Imaging Sciences 2009. 2 p. .
- [Luo and Crandall ()] 'Color object detection using spatial-color joint probability functions'. J Luo , D Crandall
   *IEEE Transactions on Image Processing* 2006. 15 (6) p. .
- [Palm ()] 'Color texture classification by integrative cooccurrence matrices'. C Palm . *Pattern Recognition* 2004.
   37 (5) p. .
- [Rao et al.] 'Content Based Image Retrievalusing Dominant Color, Texture And Shape'. M Rao , Dr B Rao , Dr
   A Govardhan . International Journal of Engineering Science and Technology IJEST.
- [Ma and Zhang ()] Content-Based Image Indexing and Retrieval, Handbook of Multimedia Computing, W Y Ma
   H J Zhang . 1999. Boca Raton, Fla, USA: CRC Press.
- [Folkers and Hanansamet (2002)] 'Content-based Image Retrieval Using Fourier Descriptors on a Logo Database'.
   Andre Folkers, Hanansamet. Proc of the 16th Int. Conf. on Pattern Recognition, (of the 16th Int. Conf. on Pattern Recognition, using Pattern Recognition Quebec City, Canada) August 2002. III p. .
- [Brodley et al. ()] 'Content-based retrieval from medical image databases: a synergy of human interaction,
  machine learning and computer vision'. C Brodley , A Kak , C Shyu , J Dy , L Broderick , A M Aisen *Proceedings of the 16th National Conference on Artificial Intelligence and the 11th Innovative Applications*of Artificial Intelligence Conference Innovative Applications of Artificial Intelligence, (the 16th National
  Conference on Artificial Intelligence Conference
- Innovative Applications of Artificial Intelligence) 1999. p. .
- [Smeulders et al. ()] 'Content-basedimage retrieval at the end of the early years'. A W M Smeulders, M Worring
   , S Santini , A Gupta , R Jain . *IEEE Transactions on Pattern Analysis and Machine Intelligence* 2000. 22
   (12) p. .
- <sup>301</sup> [Po and Do (2006)] 'Directional multiscale modeling ofimages using the contourlet transform'. D D Po , M N Do
   <sup>302</sup> . *IEEE Trans. ImageProcess* June 2006. 15 (6) p. .
- [Guo et al. ()] 'Edge analysis and identification using the continuous shearlet transform'. K Guo , D Labate , W
   Lim . Appl. Comput. Harmon. Anal 2009. 27 p. .
- [Yi et al. ()] 'Edge detection and processing using shearlets'. S Yi , D Labate , G R Easley , H Krim . Proc.
   *IEEE Int. Conference on Image Proc*, (IEEE Int. Conference on ImageSan Diego) October 12-15, 2008.
- [Liu and Yang ()] 'Image retrieval based on the texton co-occurrence matrix'. G-H Liu , J-Y. Yang . Pattern
   *Recognition* 2008. 41 (12) p. .
- [Rui et al. ()] 'Image retrieval: Current techniques, prominsigndirections, and open issues'. Y Rui, T S Huang,
   S F Chang. Journal of Visual Communication and Image Representation 1999. 10 p. .
- [Rui et al. ()] 'Image retrieval: current techniques, promising directions, and open issues'. Y Rui, T S Huang,
   S.-F Chang . 10.1109/83.336259. Journal of Visual Communication and Image Representation 1999. 10 (1)
   p. .
- [Datta et al. (2008)] 'Image retrieval: Ideas, influences, andtrends of the new age'. R Datta , D Joshi , J Li , J
   Z Wang . ACM Computing Surveys April 2008. 40 (2) p. 60.
- [Sagiv et al. ()] 'Integrated active contours for texture segmentation'. C Sagiv , N A Sochen , Y Y Zeevi .
   *IEEETransactions on Image Processing* 2006. 16 (6) p. .
- Phillip et al. ()] 'Intelligent Shape Feature Extraction and Indexing for EfficientContent-Based Medical Image
   Retrieval'. A Phillip , Nikolay M Misna , Sirakov . Proc. of IEEE Computer Based Medical Systems, (of IEEE
- 320 Computer Based Medical SystemsHouston, TX) June 23-24. 2004.
- [Khotanzad and Hongs ()] 'Invariant image recognition by Zernike moments'. A Khotanzad , Y H Hongs . IEEE
   Trans. on PatternAnalysis and Machine Intelligence 1990. 12 (5) p. .
- [Nabout ()] 'Modular Concept and Method For Knowledge Based Recognition of Complex Objects in CAQ
   Applications'. A Nabout . Series 1993. VDI Publisher. 20 (92) .

### 12 GLOBAL JOURNAL OF C OMP UTER S CIENCE AND T ECHNOLOGY

- [Smeulders (2000)] 'Pic To Seek : Combing color and shape invariant features for image retrieval'. Geverst
   Smeulders , AW . *IEEE Trans. Image Processing* Jan 2000. 91 p. .

329 [Pitas ()] Pitas . Digital Image Processing, (New York, NY, USA) 2000. John Wiley & Sons.

- [Keysers et al. ()] 'Statistical framework for modelbased image retrieval in medical applications'. D Keysers , J
   Dahmen , H Ney , B B Wein , T M Lehmann . J Electron Imaging 2003. 12 p. .
- 332 [Supervised Content based image Retrieval using Fuzzy Texton and Shearlet Transform 15. Deselaers T. Features for Image Retrieval
- Supervised Content based image Retrieval using Fuzzy Texton and Shearlet Transform 15. Deselaers T.
   Features for Image Retrieva,
- [Freeman ()] 'Techniques for the digital computer analysis of chain-encoded arbitrary plane curves'. H Freeman
   Proceedings of National Electronics Conference, (National Electronics Conference) 1961. 17 p. .
- [Do and Vetterli (2005)] 'The contourlet transform: an efficient directional multiresolution image representation'.
- 338 M N Do , M Vetterli . *IEEE Trans. Image Process* Dec. 2005. 14 (12) p. .
- [Freeman and Adelson ()] 'The design and use of steerable filters'. W Freeman , E Adelson . *IEEE Trans. Patt.* Anal. and Machine Intell 1991. 13 p. .
- 341 [Vapnik ()] The Nature of Statistical Learning Theory, V Vapnik . 1995. New York: Springer-Verlag.
- [Simoncelli and Freeman ()] 'The steerable pyramid: A flexible architecture for multi-scale derivative computa tion'. E Simoncelli , W Freeman . Proc. IEEE ICIP, (IEEE ICIPWashington, DC) 1995.
- [Chang and Li ()] 'View at Publisher ? View at Google Scholar ? View at Scopus'. Y L Chang , X Li . IEEE
   Transactions on Image Processing 1994. 3 (6) p. . (Adaptive image regiongrowing)
- [Zhang and Lu ()] 'View at Publisher ? View at Google Scholar ? View at Scopus'. D Zhang , G Lu . Pattern
   *Recognition* 2004. 37 (1) p. . (Review of shape representation and description techniques)
- 348 [Smith and Chang (1996)] 'VisualSEEk: a fully automated content-based image query system'. J R Smith, S.-
- F Chang. Proceedings of the 4thACM International Conference on Multimedia (MULTIMEDIA'96), (the
- 4thACM International Conference on Multimedia (MULTIMEDIA'96)Boston, Mass, USA) November 1996.
   p. .