Artificial Intelligence formulated this projection for compatibility purposes from the original article published at Global Journals. However, this technology is currently in beta. *Therefore, kindly ignore odd layouts, missed formulae, text, tables, or figures.* 

# Dynamic Hand Gesture Recognition of Arabic Sign Language using Hand Motion Trajectory Features Mohamed sameer Mohamed Abdalla<sup>1</sup> and Elsayed E. Hemayed<sup>2</sup> <sup>1</sup> Faculty of Engineering Cairo University *Received: 11 December 2012 Accepted: 31 December 2012 Published: 15 January 2013*

#### 7 Abstract

<sup>8</sup> In this paper we propose a system for dynamic hand gesture recognition of Arabic Sign

<sup>9</sup> Language. The proposed system takes the dynamic gesture (video stream) as input, extracts

<sup>10</sup> hand area and computes hand motion features, then uses these features to recognize the

<sup>11</sup> gesture. The system identifies the hand blob using YCbCr color space to detect skin color of

hand. The system classifies the input pattern based on correlation coefficients matching

<sup>13</sup> technique. The significance of the system is its simplicity and ability to recognize the gestures

<sup>14</sup> independent of skin color and physical structure of the performers. The experiment results

15 show that the gesture recognition rate of 20 different signs, performed by 8 different signers, is 16 85.67

17

Index terms — arabic sign language; skin color segmentation; gesture recognition; face detection; hu moments;
 correlation coefficients.

# 20 1 Introduction

gesture is a form of non-verbal communication made with a part of body, used instead of or in combination with verbal communication. Gestures are ambiguous and incompletely specified. Similar to speech and handwriting, gestures vary from a person to another, and even for the same person between different instances. Arabic Sign Language (ArSL) is a dominant Sign Language of the deaf community in Egypt, and in many other countries of the Arab world. Recognition of the gesture is difficult because of spatial variation and temporal variation among gestures performed by different signers.

Many researches have been conducted to provide appropriate methods and tools to enable deaf people to 27 interact easily and efficiently with regular people. Various sign language recognition systems have been developed 28 by manufacturers around the world to serve these people but they are neither flexible nor costeffective for the 29 end users who have difficulties communicating in verbal form. Our goal is to help these less fortunate people to 30 mingle in the society. Thus, there is a need for a system that helps in the communication between the deaf and 31 regular hearing people. To realize this system, an efficient gesture recognition method is needed, which recognizes 32 the sign language video stream for particular gesture. Since sign language is a native language, our research is 33 targeting Arabic sign language (ArSL). 34

The remainder of this paper is organized as follows; a short survey of related work is presented in Section 2. Our proposed system architecture is explained in Section 3. Followed by Section 4 where we discuss the 37 experimental results. We conclude in Section 5.

# 38 2 II.

# <sup>39</sup> 3 Related Work

Hand gesture recognition was firstly proposed by Krueger [1] as a new form of human computer interaction in
the middle of the seventies, and there has been a growing interest in it recently. Hand gestures can be classified

into two categories: static and dynamic. A static gesture is a particular hand shape and pose, represented by a
single image. A dynamic gesture is a moving gesture, represented by a sequence of images. Our approach focuses
on the recognition of dynamic gestures.

Many researchers have proposed different methods to recognize hand gestures. Two main approaches were 45 introduced to support these researches; glove-based methods [2], [3] and visionbased methods [4], [5]. The glove 46 based system [6], [2] relies on electromechanical devices. Here the person must wear some sort of wired gloves 47 that are interfaced with many sensors. Vision-based recognition systems do not use special device such as glove, 48 special sensor, or any additional hardware except simple webcam, image processing, and artificial intelligence to 49 recognize and interpret hand gestures [7], [8]. In addition, the user's motions are not limited comparing with 50 the use of glove. On the other hand, vision based systems have problems such as illumination changes, data 51 clutter and hand occlusion due to hand motion. Several researches in vision-based approaches were introduced 52 to overcome these problems. 53

The system developed by Hamada et al. [9] introduces a hand shape estimation approach to overcome occlusion by using multi-ocular images using two cameras. Tanibata et al. [10] provided a prototype approach based on feature extraction to solve hand occlusion problem for Japanese sign language recognition. The system developed by Wu et al. [11] The system developed by Tomasi et al. [12] presented 3D tracking for hand finger spelling motions by using a Real-time combination of 2D image classification and 3D motion interpolation using hand model based statistical. The system developed by Ye et al. [13] presented classifying manipulative and controlling gestures by computing 3D hand appearance using a region based coarse stereo matching algorithm.

The system developed by Lin et al. [14] presented tracking the articulated hand motion in a video sequence 61 by searching for an optimal motion estimate in a high dimensional configuration space using hand model based 62 statistics. The system developed by Feris et al. [15] proposed an approach to exploit depth discontinuities for 63 finger spelling recognition to differentiate between similarities of some signs by using multi flash camera. The 64 system developed by ?? arczak et al. [16] presented a real-time hand tracking by appearance based statistics using 65 the Viola-Jones method. This system is implemented only in a restricted single posture (hand palm). The system 66 developed by Zhou et al. [17] presented articulated object (e.g. body/hand postures) recognition using inverted 67 indexing in an image database using local image features hand model based statistics. The system developed 68 by Salleh et al. ??18] provided a good idea to convert sign language to voice recognition based on feature 69 extraction and HMM from grey scale images. Dreuw [19] investigated the use of appearance based features for 70 71 the recognition of gestures using video input. He used 1st time derivative of original images thresholded by their 72 skin probability and a camshift tracker. A finger spelling recognition method by using distinctive features of hand shape proposed by Tabata et al. [20] The system developed by Qiong et al. [21] presents detailed description of 73 a real-time hand gesture recognition system using embedded DSP board and image processing approaches. The 74 system developed by Foong et al. [22] proposed a sign to voice system prototype which is capable of recognizing 75 hand gestures by transforming digitized images of hand sign language to voice using Neural Network approach. 76 Zabulisy et al. [23] proposed a vision-based hand gesture recognition system for Human-Computer Interaction. 77

In the system developed by Xin-Yan et al. [5], a method of gesture segmentation from the video image sequence 78 based on monocular vision is presented by skin color and motion cues. The system developed by Paulraj et al. 79 [24] presented a simple sign language recognition system that has been developed using skin color segmentation 80 and Artificial Neural Network. The system developed by Hsieh et al. [25] presented a simple and fast motion 81 history image based method. In the system developed by Jiatong et al. [26] the dominant movement direction 82 of matched SURF points in adjacent frames is used to help describing a hand trajectory without detecting and 83 segmenting the hand region. The system developed by Mekala et al. [27] proposed an architecture using the neural 84 networks identification and tracking to translate the sign language to a voice/text format. Zaki and Shaheen [28] 85 presented a novel combination of vision based features in order to enhance the recognition of underlying signs. 86 They used three features; kurtosis position, principal component analysis PCA, and motion chain code. Several 87 systems have been proposed specifically for the Arabic sign language. The system developed by Mohandes [29] 88 introduced a prototype system based on support vector machine (SVM) and an automatic Translation system to 89 translate Arabic Text to Arabic Sign Language. An Arabic sign language translation system on mobile devices 90 was introduced by Halawani [30]. The system developed by Farouk et al. [31] represent a multistage hierarchical 91 algorithm for hand shape recognition using principal component analysis (PCA) as a dimensionality reduction 92 and a feature extraction method. Al-Roussan et al. [32] presented an automatic Arabic sign language recognition 93 system based on hidden Markov models. He used the discrete cosine transform to extract features from the input 94 gestures by representing the image as a sum of sinusoids of varying magnitudes and frequencies. He used 30 95 isolated words from the Standard Arabic sign language database where gloves worn by the participants were 96 marked with six different colors at six different hand regions. 97

The system developed by Nashwa et al. [33] presented an automatic translation system of gestures of the manual alphabets in the Arabic sign language. Hemayed and Hassanien [34] Dynamic Hand Gesture Recognition of Arabic Sign Language Using Hand Motion Trajectory Features introduced a new Arabic finger spelling technique that uses the edges of a segmented hand gesture as a feature vector and probabilistic neural networks to measure the similarity between the signs feature vectors.

From the previous survey of related works we find that the vision based approach is widely used for sign language recognition because of it its naturalness and low cost. Pervious works of sign language recognition 105 systems have some constraints; these constraints affect the reliability and flexibility of these systems. There is a

- still a room for improving the accuracy of recognition systems. Moreover, most pervious works for Arabic sign
- 107 language (ArSL) recognition systems deal with static hand posture.

108 The proposed system tries to eliminate some of previous systems' limitations to make the recognition process

<sup>109</sup> more practical and reliable in various conditions In this module, the hand area is extracted from the full color <sup>110</sup> image. First the system captures video stream of gesture. From this captured frames we detect the face using

111 Haar classifier [35]. The detected face location is replaced by a black ellipse to eliminate the confusion between

112 the hand and the face. The system executes accurately even if there are multiple faces in the image. The process

of face detection and removal is as shown in Fig. 1(a). [2] are used to fill in small disconnected areas. The result

- of this operation is a binary image that contains connected areas representing the hand blob. Fig. 1(c) shows
- 115 the binary image, which shows only the hand area as white color in black background.

# <sup>116</sup> 4 b) Feature Extraction Module

The output of the hand extraction stage is a binary image, which shows only the hand blob. The hand features extraction subsystem takes this binary image and find the contour shape of the hand blob as shown in Fig. 1(d). From that contour, we calculate 14 features. These features are the center of gravity for that contour (Fig. 1(e)) and then tracking the movement of hand in each frame to calculate the velocity of the hand movement and angle. In addition, the area, perimeter, orientation and 7-Hu moments features for contour shape are calculated. The

- 122 details of the features calculations are as follows:
- 123 i. Center of Gravity, Velocity and Angle Calculations
- The zeroth and first order moments [37] contain information about the center of gravity (Xc , Yc) of the object, where:
- From one frame to the next, the center is moving, say from (X1, Y1) to (X2, Y2). Then the velocity and the angle of the hand motion can be calculated as follows:
- 128 (1)(2)(3)(4)(5)(6)
- 129 Where ?"" is the angle and Vx, Vy are the corresponding velocity in x-axis and y-axis.

# $_{130}$ 5 ii. Area (A)

131 The area of a contour is the number of pixels inside this contour. The zeroth order moment describes the area 132 A of the contour of object.

133 iii. Perimeter (T)

- The perimeter of a contour is the length of curve or boundary of this contour. The contour perimeter of the object is calculated as the sum of lengths of segments between subsequent points of boundary.
- 136 Where X1,????.., XN is the boundary coordinate list.

#### 137 6 iv. Orientation

The second order moments known as the moments of inertia, can be used to determine an important image feature, orientation. In terms of moments, the orientations of the principal axes, ?, are given by Horn [38]: v.
Seven Hu Moments Hu [37] defines the seven functions, computed from central moments through order three, that are invariant with respect to object scale, translation and rotation. Therefore, these seven Dynamic Hand Gesture Recognition of Arabic Sign Language Using Hand Motion Trajectory Features functions are good features

to describe the objects.

The same Gestures may vary between performers and even for the same performer between different instances. Neither all the gestures have the same numbers of frames nor have the same start point. To provide better matching criteria for pattern matching, all the data should be normalized and interpolated. These two processes convert the original data sets into a new form, which provides better matching criteria.

# <sup>148</sup> 7 c) The Gesture Recognition Module

There are several pattern recognition techniques used for gesture recognition. In this paper we use correlation coefficient [26] technique. Correlation coefficient is a simple statistical method with short processing time and it needs only one reference sample to learn each gesture.

If we have a series of n measurements of A and B written as Ai and Bi where i = 1, 2, ..., n, then the sample correlation coefficient can be used to estimate the population correlation r between A and B as follows:

Where and are the sample means of A and B. In our system, A refers to the data set of the input gestures, B refers to the data set of the reference gestures stored in our database, and n is the number of frames in each gesture. We calculate the correlation coefficients between the input gesture and the reference gestures. The correlation coefficient is calculated for each feature separately. Then we count, for each gesture, number of correlation coefficient that is greater than a predefined threshold. In our experiments, the used threshold was 0.65. Finally the gesture with the highest count is selected as the matched gesture and its corresponding text is

160 shown to the user.

# <sup>161</sup> 8 Global Journal of Computer Science and Technology <sup>162</sup> IV.

# <sup>163</sup> 9 Results and Discussion

Due to the unavailability of a dataset for dynamic gestures from Arabic sign language, we had to build our own gestures database. We collected 20 different signs (Table 1) from eight different signers (seven males and one female) at different situations with resolution 720×480, as shown in Fig. 2. The graph shows the position of the hand's center of gravity at consecutive frames

We also analyzed the misclassification cases to measure the consistency of the proposed system. Fig. 4 shows the motion trajectory of three gestures; No 2, 8 and 17, that our system confuses them. These three gestures are very similar and their motion trajectories are very similar too. Several gestures in the Arabic sign language look similar and could be difficult to a computer vision system to differentiate between them.

In another experiment, we apply our system to the RWTH dataset developed and tested by Dreuw In our experiment, we measure the discrimination effectiveness of the proposed system by testing the recognition of each sign. Our results indicate that the recognition rate was between 80% and 100% with an average of 85.67%. Fig. ?? shows the similarity matrix between the input and reference gestures. From the shown graph, it is clear that all of the signs have high similarity with its counterpart along the diagonal axis with some minor similarity off the diagonal axis.

Figure ?? : The similarity matrix for our proposed system database and it contains 35 gestures with video 178 sequences for the signs A to Z and SCH, the German umlauts Ä, Ö, Ü and the numbers from 1 to 5. Dreuw [19] 179 achieved an error rate of 87.1% and was able to improve it to 44%. Using our proposed system, we were able 180 to achieve a better error rate of 27.6%. It was not possible to compare our work with several available systems, 181 because they differ in many aspects such as the type of data acquisition; direct measurement or vision-based. 182 Even in the vision based approach some systems require the signer to wear colored gloves. Another problem 183 arises from the lack of a common database for the evaluation of sign language recognition systems. Almost all 184 databases used by the different research groups are not publicly available. Additionally, the available databases 185 differ in language, vocabulary size, grammar restriction and selection of signs. 186 V. 187

# 188 10 Conclusion

We proposed a new gesture recognition system that can recognize the dynamic Arabic Sign Language gestures independent of skin color and physical structure of signers. In addition, the Dynamic Hand Gesture Recognition of Arabic Sign Language Using Hand Motion Trajectory Features system works in different places with normal intensity of light. The proposed features, measured from the motion trajectory of the right hand, were able to encode the gesture and to differentiate between 20 different Arabic gestures collected from eight different signers, with an average recognition rate of 85.67%. The error rate was mainly due to the high similarity between the gestures.

The proposed system was able to improve the error rate in recognizing the difficult RWTH dataset from 44% to 27.6%. In future work we will search for other clues to be able to increase the recognition accuracy especially in case of highly similar gestures. Also, handling gestures that use both hands or interfere with the face will be addressed in future work.

# 200 11 Global

201 1 2 3

 $<sup>^{1}</sup>$ © 2013 Global Journals Inc. (US) Year

 $<sup>^{2}</sup>$ © 2013 Global Journals Inc. (US) Year

 $<sup>^{3}</sup>$ © 2013 Global Journals Inc. (US)



Figure 1: F



Figure 2: F

$$x_e = \frac{M_{1,0}}{M_{0,0}}$$

Figure 3: Figure 1 :F

$$y_c = \frac{M_{0,1}}{M_{0,0}}$$

Figure 4: VolumeF

$$V_{x} = X_{1} - X_{2}$$

$$V_{y} = Y_{1} - Y_{2}$$

$$V = \sqrt{V_{x}^{2} + V_{y}^{2}}$$

$$\theta = \tan^{-1}(\frac{Y_{1} - Y_{2}}{X_{1} - X_{2}})$$
2



$$A = M_{0,0}$$

Figure 6: Figure 4 :

$$T = \sum_{i=1}^{N-1} d_i = \sum_{i=1}^{N-1} |x_i - x_{i+1}|$$

Figure 7: F

1

		(10)
(7)		
(8)		
(9)		
Gesture No.	Gesture name in Arabic	Gesture meaning in English
G1	???????? ????	WHAT IS YOUR NAME?
G2	?????	RICH
G3	??????	BRAVE
G4	???????	POTATO
G5	????? ???	EGGS
G6	????? ????	EMACIATED
G7	????? ???	MILK
G8	????? ???	NIGHT
G9	???????	hurricane -Tornado
G10	. ??????	PROPHET
G11	????? ????? ????	6 ????6 october CITY
		????
G12	????? ????	OFFICER
G13	????? ???	IMPORTANT
G14	????? ????	MANAGER
G15	??????	CLUB
G16	????? ????	ABSENT
G17	??????	DESCEND-GET DOWEN
G18	????? ????	WANT -DESIRE
G19	??????	GIVE
G20	???????	RAPIDLY -QUICKLY

Figure 8: Table 1 :

- 202 [Krueger ()] , W Krueger . Artificial Reality II 1991. Addison-Wesley.
- [Lin et al. ()] '3D model-based hand tracking using stochastic direct search method'. J Lin , Y Wu , T
   Huang . Proceedings of IEEE International Conference on Automatic Face and Gesture Recognition, (IEEE
   International Conference on Automatic Face and Gesture Recognition) 2004. p. .
- [Hemayed and Hassanien (2011)] 'A Fast edge-based arabic sign language recognition using probabilistic neural network'. E Hemayed , A Hassanien . *CiiT International Journal of Digital Image Processing* Nov. 2011. 3 (17) p. .
- 209 [Zhang et al. ()] 'A Framework for hand gesture recognition based on accelerometer and EMG sensors'. X Zhang
- X Chen , Y Li , V Lantz , K Wang , J Yang . IEEE Transactions on Systems, Man and Cybernetics-Part
   A: Systems and Humans, 2011.
- [Farouk et al. ()] 'A hierarchical algorithm for hand shape recognition'. M Farouk , A Sutherland , A Shoukry .
   *IEEE 13 th International Machine Vision and Image Processing Conference*, 2009. p. .
- [Wei et al. ()] 'A Method of hand gesture recognition based on multiple sensors'. F Wei , C Xiang , W Wen-Hui
   Z Xu , Y , V Lantz . *IEEE Bioinformatics and Biomedical Engineering* 2010.
- [Paulraj et al. ()] 'A Phoneme based sign language recognition system using skin color segmentation'. P Paulraj
   , S Yaacob , M Shuhanaz , R Palaniappan . *IEEE 6th International Colloquium on Signal Processing & Its*
- 218 Applications, 2010.
- [Hsieh et al. ()] 'A Real time hand gesture recognition system using motion history image'. C Hsieh , D Liou ,
   D Lee . *IEEE 2nd International Conference on Signal Processing Systems*, 2010.
- [Singh et al. ()] 'A Robust skin color based face detection algorithm'. S Singh , D Chauha , M Vatsa , R Singh .
   *Tamkang Journal of Science and Engineering* 2003. 6 (4) p. .
- [Sturman and Zeltzer ()] 'A Survey of glovebased input'. D Sturman , D Zeltzer . *IEEE Computer Graphics and Applications* 1994. 14 p. .
- [Mohandes ()] 'Arabic sign language recognition'. M Mohandes . Proceedings of the Conference on Imaging
   Science, (the Conference on Imaging Science) 2001. p. .
- 227 [Halawani ()] 'Arabic sign language translation system on mobile devices'. S Halawani . IJCSNS 2008. 8 (1) p. .
- [El-Bendary et al. ()] 'ArSLAT: arabic sign language alphabets translator'. N El-Bendary , H Zawbaa , M Daoud
   , A Hassanien , K Nakamatsu . *IEEE International Conference on Computer Information Systems and Industrial Management Applications*, 2010.
- [Quan ()] 'Chinese sign language recognition based on video sequence appearance modeling'. Y Quan . 5th
   International Conference on Computer Vision, 2003. p. .
- [Bao et al. ()] 'Dynamic hand gesture recognition based on SURF tracking'. J Bao , A Song , Y Guo , H Tang .
   *IEEE International Conference on Electric Information and Control Engineering*, 2011.
- [Feris et al. ()] 'Exploiting depth discontinuities for vision-based finger spelling recognition'. R Feris , M Turk
   , R Raskar , K Tan , G Ohashi . *IEEE Proceedings of the Conference on Computer Vision and Pattern Recognition Workshop 10*, 2004.
- [Tanibata et al. ()] 'Extraction of hand features for recognition of sign language words'. N Tanibata , N Shimada
   , Y Shirai . The 15th International Conference on Vision Interface, 2002. p. .
- [Tabata and Kuroda ()] 'Finger spelling recognition using distinctive features of hand shape'. Y Tabata , T
   Kuroda . 7th ICDVRAT with Art Abilitation, 2008. p. .
- [Ye et al. ()] 'Gesture recognition using 3D appearance and motion features'. G Ye , J Corso , G Hager .
   *Proceedings of CVPR Workshop on Real-Time Vision for Human Computer Interaction*, (CVPR Workshop on Real-Time Vision for Human Computer Interaction) 2004. p. .
- [Mitra and Acharya (2007)] 'Gesture recognition: A Survey'. S Mitra , T Acharya . IEEE Transactions on
   Systems, Man, and Cybernetics, Part C: Applications and Reviews May 2007. 37 (3) p. .
- 247 [Xin-Yan et al. ()] 'Gesture segmentation based on monocular vision using skin color and motion cues'. C Xin-
- Yan , L Hong-Fei , Z Ying-Yong . International Conference IEEE Image Analysis and Signal Processing,
   2010.
- [Om et al. ()] 'Hand gesture recognition: sign to voice system'. F Om , L Tj , S Wibowo . International Journal
   of Electrical 2009. p. . Computer and Systems Engineering
- [Hamada et al. ()] 'Hand shape estimation using sequence of multi-ocular images based on transition network'.
   Y Hamada , N Shimada , Y Shirai . Proceedings of the International Conference on Vision Interface, (the
- <sup>254</sup> International Conference on Vision Interface) 2002. p. .
- [IEEE Conference on Industrial Electronics and Applications ()] IEEE Conference on Industrial Electronics and
   Applications, 2010.

- 257 [Zabulis et al. ()] In Stephanidis C editor(s). The Universal Access Handbook -Human Factors and Ergonomics
- Series, X Zabulis , H Baltzakis , A Argyros . 2009. Boca Raton, FL, USA: CRC Press. p. . (Visionbased hand
   gesture recognition for humancomputer interaction)
- [Dreuw et al. ()] 'Modeling image variability in appearance-based gesture recognition'. P Dreuw, T Deselaers,
   D Keysers, H Ney. ECCV Workshop on Statistical Methods in Multi-Image and Video Processing, 2006. p. .
- [Flusser et al. ()] Moments and Moment Invariants in Pattern Recognition, J Flusser, T Suk, B Zitová. 2009.
   A John Wiley and Sons.
- [Wu and Huang ()] 'Non-stationary color tracking for vision-based human computer interaction'. Y Wu , T Huang
   *IEEE Transactions on Neural Networks* 2002. 13 (4) p. .
- [Zhou and Huang ()] 'Okapi-Chamfer matching for articulate object recognition'. H Zhou, T Huang. Proceedings
   of International Conference on Computer Vision, (International Conference on Computer Vision) 2005. p. .
- [Mekala et al. ()] 'Real-time sign Language Recognition based on Neural Network Architecture'. P Mekala , Y
   Gao , J Fan , A Davari . IEEE 43 rd Southeastern Symposium on System Theory (SSST), 2011.
- [Fei et al. ()] Realtime hand gesture recognition system based on Q6455 DSP board, Q Fei , X Li , T Wang , X
   Zhang , G Liu . 2009. IEEE Global Congress on Intelligent Systems. p. .
- [Barczak et al. ()] 'Realtime hand tracking using the Viola and Jones method'. A Barczak , F Dadgostar , M
  Johnson . Proceedings of International Conference on Image and Signal Processing, (International Conference
  on Image and Signal Processing) 2005. p. .
- 275 [Horn ()] Robot Vision, B Horn . 1986. The MIT Press.
- [Viola and Jones ()] 'Robust real-time face detection'. P Viola , M Jones . International Journal of Computer
   Vision 2004. 57 (2) p. .
- [Zaki and Shaheen ()] 'Sign language recognition using a combination of new vision based features'. M Zaki , S
   Shaheen . Pattern Recognition Letters 2011. Elsevier. 32 p. .
- [Tomasi et al. ()] 'Sign language to voice recognition: hand detection techniques for visionbased approach'. C
   Tomasi , S Petrov , A Sastry , ; J Jais . Fourth of International Conference on Multimedia and ICT in
- *Education*, 2006. p. . (Proceedings of the © 2013 Global Journals Inc. (US) 18. N. Salleh,)
- [Al-Roussan et al. ()] Videobased signerin dependent arabic sign language recognition using Hidden Markov
   Models, M Al-Roussan , K Assaleh , A Talaa . 2009. Elsevier Applied Soft Computing. p. .
- [Wu and Huang ()] 'Vision-based gesture recognition: A Review'. Y Wu, T Huang. Gesture Workshop 1999.