

# Location Based Path Guiding System for the Visually Impaired People

Mahfuzulhoq Chowdhury<sup>1</sup> and Mahfuzulhoq Chowdhury<sup>2</sup>

1

*Received: 7 December 2013 Accepted: 5 January 2014 Published: 15 January 2014*

---

## Abstract

Visually impaired or blind people faced tremendous challenges daily in accessing the information while on the move or during communicating with the world around them. They had to depend on their sighted colleagues, friends, relatives, or the people on the road to help them with locating places. Our Location Based Information System is such a location based application that works as an audio road guider for the visually impaired people using Open Street Map. Open Street Map (OSM) is a world-wide campaign for developing open source maps. Voice recognition represents a technology that is finally ready for prime time use. In our system we used voice recognition as visually impaired people unable to text searching.

---

**Index terms**— visually impaired, openstreetmap, audio direction, android.

## 1 Location based Path Guiding System for the

Visually Impaired People M. Chowdhury<sup>1</sup>, T. Alam<sup>2</sup>, P.P.Purohit<sup>3</sup> & S.A. Fahim<sup>4</sup> Visually impaired or blind people faced tremendous challenges daily in accessing the information while on the move or during communicating with the world around them. They had to depend on their sighted colleagues, friends, relatives, or the people on the road to help them with locating places. Our Location Based Information System is such a location based application that works as an audio road guider for the visually impaired people using OpenStreetMap. OpenStreetMap (OSM) is a world-wide campaign for developing open source maps. Voice recognition represents a technology that is finally ready for prime time use. In our system we used voice recognition as visually impaired people unable to text searching. The CloudMade API was used to provide multi-mode routing services together with turn-by-turn descriptions for car users, bicycle riders, and pedestrians. This solution is relatively easy and fast to deploy. This paper provides a guiding solution with detailed navigational services for visually impaired people. The experimented result demonstrates the effectiveness of our system. visually impaired, openstreetmap, audio direction, android.

## 2 I. INTRODUCTION

location-based service (LBS) is an information and entertainment service, accessible with mobile devices through the mobile network and utilizing the ability to make use of the geographical position of the mobile device. Location-based services are a general class of computer program-level services used to include specific controls for location and time data as control features in computer programs. As such (LBS) is an information and has a number of uses in Social Networking today as an entertainment service, which is accessible with mobile devices through the mobile network and which uses information on the geographical position of the mobile device.

For blind people the traditional devices to aid mobility have been the long cane and the guide dog. Although a large number of electronic mobility devices have been developed, their uptake has been very low. To help with orientation, blind people have had to rely on recognizing non-visual landmarks possibly in conjunction with an embossed map of the area.

The blind people faced tremendous challenges daily in accessing the information while on the move or during communicating with the world around them. They the people on the road to help them with locating places.

Considering this, our proposed system is design for the blind people. Most of the existing applications are for normal people and very few of them address the special requirements for the disabled people. About 15 percent of the world's population some 785 million people has a significant physical or mental disability. According to a new report prepared jointly by the World Health Organization [1] and the World Bank [2], Geneva, June, 2012 -285 million people are visually impaired worldwide: 39 million are blind and 246 have low vision. About 90% of the world's visually impaired live in developing countries. Due to growing populations and aging, these numbers are expected to double by the year 2020 making the colossal human tragedy even worse, stalling development and denying a basic human right [3].

To understand how developing mobile location services applications differs from traditional wire line applications, it is important to understand the basic principles of wireless network [4]. There are two basic of positioning a device on the market today, firstly by using satellite for example, GPS or its Russian cousin, GLONASS; secondly by using the mobile telephone network. There are also combinations of these, which increase the accuracy and decrease the cost for the user.

Global Positioning System (GPS) is based on twenty four satellites and five monitoring stations around the world. It is satellite-based navigation system, which is maintained and operated by the U.S. Department of Defense. Its primary purpose is to provide global positioning and navigation for land-based, sea-based, and air-based tactical forces, but it also been made available for commercial use [4].

GPS works by the user's receiver (which can now be made so small that they can be built into watches and cell phones) acquiring a sufficient number of satellites (a minimum of three) and triangulating them by using the travel time of the radio signal from the satellite (more properly, trilateration or resection because the system is not calculating angles). Because the position of the satellite in a space known (because the orbit and the time is known) and the distance is known (because the time it takes for the signal to get from the satellite is known, with a known velocity) the distance arc on the Earth's surface can be calculated from satellite although delays and errors that might occur when signal passes thorough the atmosphere have to be corrected. Intersecting two spheres from satellite gives an ellipsoid; applying the third satellite gives two points where the ellipsoids intersect, the intersection with fourth sphere will narrow it down to one point although usually, one of the two points is not reasonable answer and can be discarded.

Android [5], [6] is an open-source software platform developed by Google, for mobile application development on devices powered by the Android OS. It is a complete software stack that provides all the middleware needed to run end-user applications on mobile devices such as: device drivers, OS, core libraries, an optimized virtual machine, Java Native Interface (JNI), and a complete Java development environment. The blind/visually impaired people usually face the problem in finding location in any area. Hence, we have proposed a location based service on mobile phones using Open Street Map (OSM) which is mainly utilized to provide audio and visual messages on the map [7]- [9]. Open Street Map is a rapidly growing open source map of the world because of the availability of map information across the world and invent of inexpensive portable GPS devices [10]. The demand of location based services is also increasing day by day with the emerging growth of smart phones. Our proposed system is developed for both the normal and blind people. Users of our application will get audio warning message in any direction. The rest of the paper is organized as follows. In Section II, we discuss about some related works and their shortcomings. Then we present the description of proposed location based system in Section III. In Section IV, system implementation details are described. In Section V, we have discussed the experimented result. Finally, we conclude this paper stating the future plan in Section VI.

## 3 II. RELATED WORKS

There exists some research works for helping blind people with map technology. Some modifications of these applications are required so that blind people can use these smoothly. An android platform based mobile application using OSM to help visual impaired and normal people was proposed in [11]. This application helps users to search a specific location with text. This system can't give audio direction to reach his/her destination and failed to give audio message if he/she on wrong path. One of the mentionable existing research works was Walky-Talky [12]. This application has been designed to help the blind with walking directions that combine Google Maps with GPS navigation technology. The main weakness of this project was it uses Google Map. Google Map has legal or technical restrictions on its use, holding back people from using it in creative, productive, or unexpected ways. System proposed in [4] and [13] can't consider audio based path finding help. RFID-based system for navigation in a building for blind or visually impaired people was proposed in [14]. This system can't work for outdoor users.

## 4 III. METHODOLOGY a) Overview of the Overall System

The aim of our work is to help visually impaired people with audio to reach his/her destination. Fig. 1 demonstrates the workflow of our proposed location based system for the visually impaired people. The application demands a GPS enabled android mobile. GPS must be enabled before start the application. Network provider is another system which can generate location information to the device from the network operator. In our application we need accurate data of a position. We used GPS provider and Network provider both. We have got starting geopoint from network provider and GPS provider and destination geopoint from the user. These

---

geopoints will be generated to the Cloudmade API. There are some formats to generate data to the Cloudmade API. We have selected language English and distance in miles and API 0. Parsing XML from the internet is a pretty common requirement on any platform. There are numerous ways to accomplish this task on every language out there, and the Android platform is no exception. On the Android, this is accomplished using SAXParser, a serial access parser API for XML. SAXParser functions as a stream parser, with an eventdriven API, using callback methods that trigger every time events occur during the reading. The majority of the work is done by a SAX-Handler. The SAXParser will walk through the XML file from beginning to end (hence parsing is always unidirectional) and calls appropriate handler methods along the way. For this exercise, we will create a Handler that extends org.xml.sax.helpers. DefaultHandler and overrides the necessary methods.

On the start/end of each document, the following methods get called: In this case, localName will be `\exampletag`". The `atts` variable will hold any associated attribute information: `atts.getValue(\name")` will return `\labs`". When we reach a closing tag, like `<=exampletag>`, the equivalent closing method gets called: `public void endElement(String namespaceURI, String localName, String qName) throws SAXException {}`.

In between an opening and closing tag, there can be a string, like `<exampletag>here is some content<=exampletag>`. The SAXParser reads in the string, one character at a time, but buffers method calls to the handler: `public void characters(char ch[], int start, int length) {}`.

The `ch[]` array holds a buffer of characters that the SAXParser has read in, but the only relevant chunk is given by the start and length values. With large enough strings, the `characters()` method may be called multiple times within a single block of character data. This is a place where we personally stumbled with, as it seems many tutorials out there seem to ignore this fact, assuming the entire block is returned and end up only getting partial data.

## 5 e) Audio Direction

In the result our application will generate audio direction at every turn of a road. We got geopoints of every turn but we take a round area by taking the geopoint as a center. By Haversine formula [15] we find out the distance between two geopoints and we took 5 meters as its range. We used an algorithm to generate the audio message when user reaches to the area. We used a thread to perform task in background and on progress of the application. After three days of testing period, they acclaimed that the system is much more helpful to find their destination. They found the system much more helpful as they didn't have to search their destination with text typing. Although they were on wrong direction they got new direction from the application. When the volunteer reaches within an area they got audio message. They didn't have to be attentive on their way for searching turn of road.

Criticisms: But still they (users) have some complaints. Volunteer-2 said that it is very slow. We said him, due to slow internet connection it works slowly. They also got some problems in running the application. The application became stop when there is no route in Cloudmade API for given geopoints. We said them about our limitations, in our country OpenStreetMap is not well developed like Google map. Besides, all the routes are not developed to get shortest path and direction of road.

## 6 c) Our Feedback

We have considered all the problems and suggestions from our experiment and fixed the problems. The following solutions of problems are fixed in the new version of our software. Firstly, the speed of speech engine is now maintained so that users can comfortably recognize the audio. Secondly, the distance of two positions is maintained. We hope our new version will now satisfy all the users and perfectly applicable to the real environment.

## 7 VI. CONCLUSION

Our location based system mainly developed for the visually impaired people. Our application helps visually impaired people to reach his/her destination with a shortest path. It generates voice before reaching the turn of road so that user can be aware of the turn of road. There are some limitations for the application to run in developing country. Our total work depends on internet speed. In developing country it is very costly to generate high speed internet. Lack of details on OSM of Bangladesh is the main challenge of our work. The more volunteers working on OSM can make map of the country rich. In that case, our application will perform better in the context of Bangladesh. Moreover, we have future plan to implement another application that will generate suitable path for visually impaired/blind people to reach his/her destination by observing traffic jam and weather. Finally, our proposed system has opened further research so that anyone from any part of the world can work on the existing system and incorporate their ideas with it.

---

<sup>1</sup>© 2014 Global Journals Inc. (US)

<sup>2</sup>© 2014 Global Journals Inc. (US) Location Based Path Guiding System for the Visually Impaired People



Figure 1: Figure 1 :




Figure 2: Figure 2 :

---

3




Figure 3: Figure 3 :

4




Figure 4: Figure 4 :




Figure 5: Figure 5 :



Figure 6: Figure 6 :




Figure 7:

```

<rtept lat="22.462374" lon="91.973289">
<desc>Head south, 98 ft</desc>
<extensions>
<distance>30</distance>
<time>7</time>
<offset>0</offset>
<distance-text>98 ft</distance-text>
<direction>S</direction>
<azimuth>180.0</azimuth>
</extensions>
</rtept>
<rtept lat="22.462105" lon="91.973297">
<desc>Turn right, 0.1 miles</desc>
<extensions>
<distance>216</distance>
<time>52</time>
<offset>2</offset>

```

7

Figure 8: Figure 7 :



Figure 9:



---

157 [ Android ] , Android . <http://developer.android.com/guide/basics/what-is-android.html>  
158 [Androiddeveloper] , Androiddeveloper . [http://developer.android.com/guide/developing/](http://developer.android.com/guide/developing/devices/emulator.html)  
159 [devices/emulator.html](http://developer.android.com/guide/developing/devices/emulator.html)

160 [Chumkamon et al. ()] ‘A Blind Navigation System Using RF-ID for Indoor Environments’. P Chumkamon , P  
161 Tuvaphanthaphiphat , Keeratiwintakorn . *Electrical En-gineering/Electronics, 5th International Conference*  
162 *on Computer, Telecommunications and Information Technology*, May 14-17, 2008.

163 [Bing aerial imagery in OSM Available : [<http://wiki.openstreetmap.org/wiki/Bing>, retrieved: 9 (December-12)]  
164 ‘Bing aerial imagery in OSM’. Available : [<http://wiki.openstreetmap.org/wiki/Bing>, retrieved: 9, December-  
165 12.

166 [Moller et al. (2009)] ‘Enhanced Perception for Visually Impaired People’. Moller , Toth , Wang , Moller , Arras  
167 , Bach , Guttman Schumann . *3rd International Conference on Bioinformatics and Biomedical Engineering*,  
168 June, 2009. p. .

169 [Haversineformula] <http://en.wikipedia.org/wiki/Haversineformula> *Haversineformula*,

170 [Rifat and Ahmed ()] ‘Location based Information System using OpenStreetMap’. Moutushy Rifat , Ferdous  
171 Ahmed . *Research and Development (SCORED), IEEE Student Conference*, Dec. 19-20, 2011.

172 [Devaraju (2004)] *Location Based Service*, A Devaraju . [http://ifgi.unimuenster.de/~deva01/images/](http://ifgi.unimuenster.de/~deva01/images/Anusuriya.pdf)  
173 [Anusuriya.pdf](http://ifgi.unimuenster.de/~deva01/images/Anusuriya.pdf) September 2004. (Und-ergraduate Thesis)

174 [Zheng et al.] ‘Mobile routing services for small towns using cloudmade api and OpenStretMap’. Jianghua Zheng  
175 , Xiaoyu Chen , Blazej Ciepruch , Adam C Winstanley , Peter Mooney , Ricky Jacob . *The International*  
176 *Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences*, Part 38 p. .

177 [ProjectHaiti] [http://wiki.openstreetmap.org/wiki/WikiProject\\_Haiti](http://wiki.openstreetmap.org/wiki/WikiProject_Haiti) *ProjectHaiti*,

178 [ProjectLibya] [http://wiki.openstreetmap.org/wiki/WikiProject\\_Libya](http://wiki.openstreetmap.org/wiki/WikiProject_Libya) *ProjectLibya*,

179 [The World Health Organization website] *The World Health Organization website*, <http://www.who.int/en/>